

Fusion



















Fusion

This new article Fusion is part of our Comfort Collection. This heavy jacquard woven quality is a valuable addition to this collection of soft and elegant fabrics, all rich in volume.

Developed by our dedicated team as a fabric that will lift the appearance of any furniture item on its own. The dessin is subtle and can be styled both as an interior basis or accent fabric. For example, in combination with other Textaafoam fabrics such as Challenger, Shout or Leaf.

Fusion offers a heavy and chunky quality while the chenille yarns create an elegant, soft and full hand feel. This fabric is perfect for both loose covers and tight fitted upholstery.

To create the voluminous and luxury appearance we used heavy chenille yarns. Typically, seat depression and shading are possible. With loving care during use this can be minimalized. This article is washable at 30 degrees Celsius.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing,

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside n/a / chenille jacquard

Suitable for



Please note: colours may vary according to your screen settings.





wood 108

Fusion - Article passport

A voluminous jacquard woven quality with heavy chenille yarns creates a soft, elegant and full hand feel.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics	
-------------------------	--

1 Todact characteristics		
Productgroup	chenille jacquard	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	n/a	
Coating	sbr	
Statistic code	54075200	
Dyeing method	piece dyed	
Available colours	19	
Packaging	bubble wrap	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09		
				Dry	Wet	DGM	DGM+			
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	85.000		min. 8.000	min. 16.000	А		
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4	-5	min. 3-4	min. 4	А		
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5									
	light colours	CTL	L grade 5				min.5	В		
	middle colours	CTL	grade		5	min. 4	min.5	В		
	dark colours	CTL	grade	5		min. 4	min.5	В		
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11	DIN EN ISO 105-X12:2016-11								
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
	dark colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
gnitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	СТЬ		pas	sed					

Processing specifications

-	T+	Forested by	11-24	T t It	N DAL CZ 420/4-2040 04	No DIN FN 4
Material weight in grams per linear meter	± 580					
Roll length in meters	± 30					
Minimum workable width in centimeters	± 138					
1 Toccooming Specimentations						

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.124	1.139	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	85,9	70,6	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,0	2,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed certified				
	Oeko-Tex, product class II	Centexbel						

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,4	0,0	n/a	n/a	A/A











- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.















creativity in fabrics

Textaafoam b.v.La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands