

Juke























Juke

Juke, a heavy knitted velvet in our Textaafoam Comfort Collection. A Collection that stands for softness, volume and elegance. Juke will suit all kinds of upholstery: beds, chairs, sofa's and more specific projects.

Piece dyed, treated to be moisture and stain resistant and machine washable at 30 degrees Celsius, Juke is easy to clean. Its longer pile provides enormous softness with a rather shiny and elegant look. This puts Juke among the most wanted articles in our market.

Available from stock in a broad range of contemporary colours. Packed with care in suspended boxes for full rolls or bubblewrap for exact meters to avoid lasting pressure marks during storage and transport.

- Please note that no fluor-carbon treatment has been used for this quality, due to the production and dyeing method it is automatically damp & dirt prevented, stain resistant and easy to clean & maintain.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside 90%PES 10%CO / knitted velvet

Suitable for



Please note: colours may vary according to your screen settings.



Please note: colours may vary according to your screen settings.



Please note: colours may vary according to your screen settings.





winered 39

Juke - Article passport

Dyeing method

Available colours

Packaging

Article with an enormous softness with a rather shiny and elegant look.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics					
Productgroup	knitted velvet				
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery				
Composition faceside	100%PES				
Composition backside	90%PES 10%CO				
Bonding	woven				
Statistic code	60019200				

piece dyed

43 boxes

Durability specifications								
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	ı
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	100.000		min. 20.000	min. 40.000	А
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	5		min. 3-4	min. 4	А
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	В
	middle colours	CTL	grade	4-5		min. 4	min.5	B-C
	dark colours	CTL	grade	4		min. 4	min.5	С
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4	4	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/A
gnitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	СТL		passed				

Processing specifications								
Minimum workable width in centimeters	± 138							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 560							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	638	690	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	77,8	90,8	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,0	2,3	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	13,0	12,2	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		pas	ssed			
	Oeko-Tex, product class II	Centexbel		cert	ified	1		

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,8	-1,6	n/a	n/a	A/A





























creativity in fabrics

Textaafoam b.v.La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934 F +31(0)13 534 7586 E info@textaafoam.nl www.textaafoam.nl